

RECEIVED
CENTRAL FAX CENTER
OCT 12 2007

PATENT
P56961

IN THE CLAIMS

Pursuant to 37 CFR §121(c), the claim listing, including the text of the claims, will serve to replace all prior versions of the claims, in the application.

Please amend Claims 1, 6 and 11, as follows:

1. (Currently Amended) A system for extending a distance of x Digital Subscriber Line using a reserved telephone line, comprising:

a Customer-Provided Equipment for supplying an x Digital Subscriber Line transmission service to a subscriber terminal;

a Digital Subscriber Line Access Multiplexer setting an initial link with the Customer-Provided Equipment for an x Digital Subscriber Line transmission service, and transceiving data with the Customer-Provided Equipment through the set link; and

a distance extension module being installed with at least ~~more than~~ one module between the Digital Subscriber Line Access Multiplexer and the Customer-Provided Equipment, in order to receive x Digital Subscriber Line transmission data from the Digital Subscriber Line Access Multiplexer in connection with an optional reserved telephone line selected from telephone line bundles incoming from the Digital Subscriber Line Access Multiplexer, and after separating the received transmission data, to transmit the separated transmission data to a module of a back end or the Customer-Provided Equipment, or to transmit transmission data received from the module of the back end or the Customer-Provided Equipment.

2. (Original) The system of claim 1, wherein each distance extension module, comprising:

PATENT
P56961

3 a Customer-Provided Equipment module receiving x Digital Subscriber Line
4 transmission data from the Digital Subscriber Line Access Multiplexer by being
5 connected to each of reserved telephone lines among telephone line bundles incoming
6 from the Digital Subscriber Line Access Multiplexer or a distance extension module of a
7 front end, and separating the received transmission data or transmitting optional x Digital
8 Subscriber Line transmission data to the Digital Subscriber Line Access Multiplexer;

9 a Central Office module transmitting the transmission data separated through the
10 Customer-Provided Equipment module to a distance extension module of a back end or
11 the Customer-Provided Equipment in order to extend the x Digital Subscriber Line
12 distance, or transmitting transmission data received from the distance extension module
13 of the back end or the Customer-Provided Equipment to the Customer-Provided
14 Equipment; and

15 a controller setting an initial link between the Customer-Provided Equipment
16 module and the Digital Subscriber Line Access Multiplexer or the Central Office module
17 of the distance extension module of the front end, setting an initial link between the
18 Central Office module and the Customer-Provided Equipment module of the distance
19 extension module of the back end or the Customer-Provided Equipment, transmitting set
20 link information to the Digital Subscriber Line Access Multiplexer, and relaying the
21 transmission data between the Customer-Provided Equipment module and the Central
22 Office module.

1 3. (Original) The system of claim 1, wherein the Digital Subscriber Line Access
2 Multiplexer includes a controller for setting the initial link with the neighboring distance
3 extension modules, receiving the link information set between the distance extension

PATENT
P56961

4 module and the Customer-Provided Equipment, and setting a link to the
5 Customer-Provided Equipment.

1 4. (Original) The system of claim 1, wherein the distance extension module uses
2 reserved telephone lines installed in a home distributor or a terminal box.

1 5. (Original) The system of claim 4, wherein the home distributor or the terminal
2 box uses reserved telephone lines including a Customer-Provided Equipment distribution
3 module for connecting with a home telephone network by being connected to a main line
4 of telephone line bundles from the Digital Subscriber Line Access Multiplexer or the
5 distance extension module of the front end.

1 6. (Currently Amended) A method for extending a distance of x Digital
2 Subscriber Line using a reserved telephone line, comprising:

3 supplying an x Digital Subscriber Line transmission service to a subscriber
4 terminal by a Customer-Provided Equipment;

5 setting an initial link with the Customer-Provided Equipment for an x Digital
6 Subscriber Line transmission service, and transceiving data with the Customer-Provided
7 Equipment through the set link by a Digital Subscriber Line Access Multiplexer; and

8 installing a distance extension module with at least ~~more than~~ one module between
9 the Digital Subscriber Line Access Multiplexer and the Customer-Provided Equipment,
10 in order to receive x Digital Subscriber Line transmission data from the Digital
11 Subscriber Line Access Multiplexer in connection with an optional reserved telephone
12 line selected from telephone line bundles incoming from the Digital Subscriber Line

PATENT
P56961

13 Access Multiplexer, and after separating the received transmission data, to transmit the
14 separated transmission data to a module of a back end or the Customer-Provided
15 Equipment, or to transmit transmission data received from the module of the back end or
16 the Customer-Provided Equipment.

1 7. (Original) The method of claim 6, with each distance extension module,
2 comprising:

3 receiving, by a Customer-Provided Equipment module, x Digital Subscriber Line
4 transmission data from the Digital Subscriber Line Access Multiplexer by being
5 connected to each of reserved telephone lines among telephone line bundles incoming
6 from the Digital Subscriber Line Access Multiplexer or a distance extension module of a
7 front end, and separating the received transmission data or transmitting optional x Digital
8 Subscriber Line transmission data to the Digital Subscriber Line Access Multiplexer;

9 transmitting, by a Central Office module, the transmission data separated through
10 the Customer-Provided Equipment module to a distance extension module of a back end
11 or the Customer-Provided Equipment in order to extend the x Digital Subscriber Line
12 distance, or transmitting transmission data received from the distance extension module
13 of the back end or the Customer-Provided Equipment to the Customer-Provided
14 Equipment; and

15 setting, by a controller, an initial link between the Customer-Provided Equipment
16 module and the Digital Subscriber Line Access Multiplexer or the Central Office module
17 of the distance extension module of the front end, setting an initial link between the
18 Central Office module and the Customer-Provided Equipment module of the distance
19 extension module of the back end or the Customer-Provided Equipment, transmitting set

PATENT
P56961

link information to the Digital Subscriber Line Access Multiplexer, and relaying the transmission data between the Customer-Provided Equipment module and the Central Office module.

8. (Original) The method of claim 7, wherein the Digital Subscriber Line Access Multiplexer comprises setting, by a controller, the initial link with the neighboring distance extension modules, receiving the link information set between the distance extension module and the Customer-Provided Equipment, and setting a link to the Customer-Provided Equipment.

9. (Original) The method of claim 7, wherein the distance extension module uses reserved telephone lines installed in a home distributor or a terminal box.

10. (Original) The method of claim 9, wherein the home distributor or the terminal box uses reserved telephone lines including a Customer-Provided Equipment distribution module for connecting with a home telephone network by being connected to a main line of telephone line bundles from the Digital Subscriber Line Access Multiplexer or the distance extension module of the front end.

11. (Currently Amended) A system for extending a distance of x Digital Subscriber Line using a reserved telephone line, comprising:

a first unit supplying an x Digital Subscriber Line transmission service to a subscriber terminal;

a second unit setting an initial link with the first unit for an x Digital Subscriber

PATENT
P56961

6 Line transmission service, and transceiving data with the first unit through the set link;
7 and

8 a third unit being installed with at least ~~more than~~ one module between the Digital
9 Subscriber Line Access Multiplexer and the first unit, in order to receive x Digital
10 Subscriber Line transmission data from the second unit in connection with an optional
11 reserved telephone line selected from telephone line bundles incoming from the second
12 unit, and after separating the received transmission data, to transmit the separated
13 transmission data to a module of a back end or the first unit, or to transmit transmission
14 data received from the module of the back end or the first unit.

1 12. (Original) The system of claim 11, wherein each third unit, comprising:

2 a fourth unit receiving x Digital Subscriber Line transmission data from the
3 Digital Subscriber Line Access Multiplexer by being connected to each of reserved
4 telephone lines among telephone line bundles incoming from the second unit or the third
5 unit of a front end, and separating the received transmission data or transmitting optional
6 x Digital Subscriber Line transmission data to the second unit;

7 a fifth unit transmitting the transmission data separated through the fourth unit to a
8 distance extension module of a back end or the first unit in order to extend the x Digital
9 Subscriber Line distance, or transmitting transmission data received from the distance
10 extension module of the back end or the first unit to the first unit; and

11 a sixth unit setting an initial link between the fourth unit and the second unit or the
12 fifth unit of the distance extension module of the front end, setting an initial link between
13 the fifth unit and the fourth unit of the third unit of the back end or the first unit,
14 transmitting set link information to the second unit, and relaying the transmission data

PATENT
P56961

15 between the fourth unit and the fifth unit.

1 13. (Original) The system of claim 12, wherein the second unit includes a
2 controller for setting the initial link with the neighboring third units, receiving the link
3 information set between the third unit and the first unit, and setting a link to the first unit.

1 14. (Original) The system of claim 13, wherein the third unit uses reserved
2 telephone lines installed in a home distributor or a terminal box.

1 15. (Original) The system of claim 14, wherein the home distributor or the
2 terminal box uses reserved telephone lines including a Customer-Provided Equipment
3 distribution module for connecting with a home telephone network by being connected to
4 a main line of telephone line bundles from the second unit or the third unit of the front
5 end.